GLIDERMATIC GTS

- 1. Remove the light cover from the motor
- 2. Locate the remote programming button on the motor's circuit board (Please refer to pictures)
- 3. Press the program button on the motor once and immediately release this button. A red light will illuminate (If the red light does not illuminate beside the button you have just pushed then this is the wrong button)
- 4. In less than 5 seconds, push and hold button A or button 1 on the new remote
- 5. The red light will go out and the remote is coded





GLIDEROL GRD

- 1. Remove the cover from the motor wall unit
- 2. Located the remote programming button on the motor's circuit board (Please refer to pictures)
- 3. Press the program button on the motor once and immediately release this button. A red light will illuminate (If the red light does not illuminate beside the button you have just pushed then this is the wrong button)
- 4. In less than 5 seconds, push and hold button A or button 1 on the new remote
- 5. The red light will go out and the remote is coded







Please Note: If you have more than one motor, you will use button A or button 1 for all motors and the motor will determine which button on the remote will operate the door.

WARNING

To prevent possible SERIOUS INJURY or DEATH:

- NEVER allow small children near batteries.
- If battery is swallowed, immediately notify a doctor.
- To reduce risk of fire, explosion or chemical burn:
- Replace ONLY with the same size and type battery

- DO NOT recharge, disassemble, heat above 100° C or incinerate